LEGEND METAL SEATING CONSTRUCTION -

- \cdot Fully welded chair frame is constructed of 14 gauge 1 1/2 x 1/2", 1 1/2 x 3/4" and 1 x 1" steel tubing, and 1/8" and 3/16" thick formed steel components and powder coated for long life
- · Contoured back panel is constructed of laminated, high density hardwood veneers using a RF process and a UF resin with very low off gas emissions
- · Plywood seat panel is covered with a hytrel elastomer composite that retains its original shape
- · Foam contains environmentally-friendly bio-based materials, and is California TB117-2013 Compliant

FEATURES -

- Fully welded design ensures long-term structural integrity
- · All fasteners are tamper-resistant
- · Wallsaver leg design protects walls from damage
- · Nylon glides are non-removable and protect floors from damage

OPTIONS -

- · Custom frame and arm cap finishes
- · Choice of wood, polyurethane or solid surface arm caps
- · Contrasting fabrics

Bolt-to-floor brackets

· Added weight

· Moisture barrier



24.5

25.25

34.25

18

21

1

1

26.5

0.75

50 lbs

500 lbs





arms

24.5

25.25

34.25

18

21

1

2

26.5

0.75

50 lbs

500 lbs









LHD-21 Guest Chair

LHD-21-CAF Guest Chair, fully closed

LHD-24 Guest Chair

27.5

25.25

34.25

18

24

1

1

26.5

0.75

54 lbs

500 lbs







LHD-31-CAF			
Guest Chair, fully closed			

Guest Chair, fully closed arms	Guest Chair	Guest C arms
27.5	34.5	34.5
25.25	25.25	25.25
34.25	34.25	34.25
18	18	18
24	31	31
26.5	26.5	26.5
1	1.75	1.75
0.75	1.25	1.25
2	1	2
54 lbs	65 lbs	65 lbs
500 lbs	750 lbs	750 lbs



	LTF-1818-16-BH Free Standing Table	LTF-1842-16-BH Free Standing Table
Width	18	18
Depth	18	42
Height	16	16
Weight	24 lbs	42 lbs

T +1 877 395 2623

F +1 877 395 6270

45 Goodrich Drive, Kitchener ON, N2C 0B8

Width

Depth

Height

Seat Height

Seat Width

Arm Height

Ship Weight

Weight Rating*

COM Yard Back

COM Yard Seat

COM Yard Arms

E sales@stancehealthcare.com stancebh.com



* Certified to BIFMA X5.4–2012 Standard. Weights listed are extrapolated from the Seating Durability and DropText procedures of this standard.

